

Introduction

The purpose of this guide is to provide instructions for installing Kernel Toolkit (also referred to as "Toolkit") Version 7.3.

The following minimum software versions are required to install this package:

**Kernel V. 7.1
VA FileMan V. 20.0
MailMan V. 7.0
DSM for OpenVMS V. 6.2
MSM-PC V.4.0.n**

Instructions are provided for three operating systems (OS):

**DSM for OpenVMS
MSM-PC V.4.0.n
M/SQL**

Toolkit Version 7.3 also supports MSM-UNIX and DataTree MUMPS (Massachusetts General Hospital Utility Multi-Programming System).

The installation steps provided in this guide apply to all the supported operating systems. (Global protection does not apply for DataTree systems.)

NOTE:

- **for M11+, operating system version 3.6 or above is required**
- **for M/VX, version 5B or above is required (the Kernel Toolkit init will not run if previous OS versions are present).**

When using this manual, it is recommended that you highlight the commands corresponding to your operating system for easy summary viewing (e.g., highlight the box labeled DSM for OpenVMS, MSM, etc.). Also note that in these instructions, "VAH" refers to the Production account and "MGR" refers to the Library or Manager account. You may use different names at your site and should pencil them in to avoid confusion later on. Also note that for M/SQL systems, a volume set is a directory set. For MSM, a volume set is called a volume group.

New Globals

The following global is new with Toolkit V. 7.3:

- ^XUCS** The ^XUCS global houses the files for the MSM-PC Performance Monitor (MPM). This new global will not exist in non-MSM sites. Automatic purging can be enabled for this file.

The following globals were new with Toolkit V. 7.2 and must be in place for Toolkit V. 7.3:

- ^XT** The ^XT global is the location for all files related to Multi-Term Look-Up (MTLU). This global should reside in the Production account (VAH).
- ^XUCM** The ^XUCM global contains the files for the VAX/Alpha Performance Monitor (VPM) and can be expected to grow at approximately 80 kb/day/node until you purge. Automatic purging can be enabled for this file. This global should reside in the Production account (VAH) in a cluster-mounted volume set.

NOTE 1: During this installation, a VPM pre-init converts the first subscript of ^XUCM to match the file number.

NOTE 2: With Toolkit V. 7.3 the ^XUCP global is no longer used for storage of Resource Usage data. DSM for OpenVMS sites can remove ^XUCP from their system. Data from the Resource Usage module now stores raw data in ^XTMP("XUCP"). Global growth is dependent on the amount of activity on your system and could be substantial. If running this module for the first time, we recommend running for brief periods (1-2 hour sessions) until you are more familiar with its behavior.

Installing Toolkit V. 7.3

Preliminary Considerations

1. Kernel V. 7.1 must be in place before installing Toolkit V. 7.3.
2. Your distribution media contains the following files:

KTK7_3.RTN (Kernel Toolkit, version 7.3)

K71PAT40.RTN (Kernel 7.1 patch #40)
3. This document assumes you have not yet installed Kernel V. 8. However, **for Kernel V. 8 sites the following information is important:**
 - a. **Do not apply the Kernel 7.1 patch (#40).** These are the routines contained in the file K71PAT40.RTN.
 - b. Verify that you have cleaned up your Production account of the unused Kernel Manager Routines. In particular, remove ZTMGRSET, ZOSV* and ZOSF*.
 - c. When instructed to move the Z* routines from VAH to MGR, some routines will no longer exist. This is okay.
 - d. When instructed to run TOOLKIT^ZTMGRSET, the version for Kernel V. 8 will not ask you for input. This entry point only renames Toolkit routines to their "%" names.

4. For all Kernel V. 7.1/Toolkit V. 7.2 sites, **excluding Kernel V. 8 sites**: Apply Kernel 7.1 patch #40 to your Production account of the appropriate CPUs.

```
NXT,KDE>D ^%RR

Routine Restore

Input Device ? > K71PAT40.RTN

Restoring routines from USER$:[KERNEL.TK73BLD]K71PAT40.RTN;2

Saved by %RS from [NXT,KDE] on 22-FEB-1995 16:31:34.25
Header: Kernel 7.1 Patch #40

Restore All (A), Selected (S), or Confirm on overwrite (C) ? <A> <RET>

XGF      XGFDEMO  XGFDEMO1  XGKB      XGS      XGSA      XGSBOX    XGSETUP
XGSW     XPDMENU  XPDUTL    ZOSV1DTM  ZOSV1GTM ZOSV1VXD  ZOSV2MSM  ZOSV2VXD
ZOSVDTM  ZOSVGTMT  ZOSVM11P  ZOSVMSM   ZOSVMVX  ZOSVVXD   ZTBKC     ZTBKCDTM
ZTBKCMPT ZTBKCMSM  ZTBKCMVX  ZTBKCVXD  ZTMGRSET

29 routines saved
```

Copy the following routines to your corresponding Manager account(s):

ZOSV*
ZTBK*
ZTMGRSET

These routines and others will be renamed to "%" routines later in the installation. Review and complete all other "preliminary" steps that apply to your platform, then begin the installation.

5. Skills required to perform the installation are listed below. Instructions for performing these functions are provided in Vendor-supplied operating system manuals as well as Decentralized Hospital Computer Program (DHCP) publications.
6. DSM for OpenVMS instruction is provided in the *VAX DSM Systems Guide (Cookbook)*
7. MSM-PC instruction is provided in the *486 Cookbook and MSM System Managers Guide*.
8. You need to know how to:
 - Log onto the system console.

- **Shutdown and bring up (boot) the system.**
- **Load a magtape/diskpack and use the tape drive/disk drive.**
- **Enable/disable routine mapping and translate/implicit/replicate globals.**
- **Run a system status and restore a job.**
- **Copy routines using: diskettes, tapes, SDP space (PDP) or VMS files (VAX).**
- **Backup the system.**
- **Global management: enable/disable journaling, global placement, protection.**
- **Switch User Class Identification (UCI) from Manager (MGR) to Production (VAH).**

MSM Sites

Your MUMPS implementation includes a %INDEX utility. This utility is similar to the one by the same name that is distributed with the Kernel Toolkit. It is important to note that:

- When loading Kernel Toolkit onto an MSM system, you overwrite the MSM %INDEX utility with the Kernel Toolkit's %INDEX utility.
- Consequently, whenever you update your copy of MSM you overwrite the Kernel Toolkit's %INDEX utility with the MSM %INDEX utility.

If you prefer using the Kernel Toolkit's version of %INDEX, remember to reload it whenever you update your copy of MSM.

The Kernel Toolkit %INDEX utility is exported in the ZINDEX* routines and can be restored as follows:

- **In MGR: Restore %INDEX.**
After loading a new version of MSM, restore the Kernel Toolkit's like-named utility if its functionality is preferred.

MSM

```
>D RESTORE^ZINDEXH
```

NOTE: The Kernel Toolkit's %INDEX utility accommodates VA standards as well as the 1990 ANSI MUMPS Standard.

The XIND* routines have been supplied to perform %INDEX on applications requiring the Type A extension to the 1990 ANSI MUMPS Standard.

These routines can be run directly (D ^XINDEX) and should not be placed in your Manager's account.

Advance Preparation

- **Back up your system as a safeguard before the installation.** Optionally, for future reference, you may also want to save a list of your Kernel routines by running a routine directory (D ^%RD) for the Kernel namespaces (X*, Z* subtracting out ZZ*).
- **Load the routines into a test account and run the NTEG routine listed below.** If you have received a patched routine set, those patched routines are identified as being off by the number of bits that correspond to the patch and the affected routine(s) should have been noted in a cover letter. Exceptions to this should be reported to your ISC.

```
>D ^XTNTEG
```

- **Global Placement:**

^XT

The ^XT global was new with Toolkit V. 7.2 and is the location for all files related to Multi-Term Look-Up (MTLU).

In VAH: If ^XT is not already placed, it should be placed in the appropriate volume set. Translate ^XT across all CPUs.

^XUCM

For Alpha sites only, the ^XUCM global was new with Toolkit V. 7.2 and contains the files for the VAX/Alpha Performance Monitor (VPM). It can be expected to grow at approximately 80 kb/day/node until you purge.

In VAH: If ^XUCM is not already placed, it should be placed in the appropriate volume set. Translate ^XUCM across all CPUs.

^XUCS

For MSM sites only, Toolkit V. 7.3 brings in a *new* global, ^XUCS. This global houses the files for the MSM-PC Performance Monitor (MPM).

In VAH: MSM sites should place the ^XUCS global in an appropriate volume set. If your site has more than one volume set, translate ^XUCS across all CPUs.

Automatic purging can be enabled for the ^XUCM and ^XUCS files.

- **Global Protection:**

The global ^XUCS is used only by the MSM performance monitor and is new with Toolkit V. 7.3.

For MSM, verify that protection on the globals ^XT and ^XUCS is:

System: RWD
World: RWD
Group: RWD
User: RWD

For Alpha systems, the recommended protection for the ^XT and ^XUCM globals is:

System: RWP
World: RW
Group: RW
UCI: RWP

VAX/ALPHA Installations

NOTE: 486 sites may skip this topic and continue with the "MSM-PC Installations" topic that follows.

The following steps are required to support the VAX/Alpha Performance Monitor (VPM):

- TaskMan *must* be set up to run from a DCL context. When run from a DCL context TaskMan runs as a privileged VMS user. The manager runs in DSM as a job that originated in a node-specific VMS batch queue and, by default, submits new submanagers to the same queue as needed. When a program calls ^ZTLOAD it is possible to request that the job be run on a *specific* CPU/Node in your cluster. The manager "submits" the job as a new submanager to that node-specific batch queue. This allows the programmer to control which CPU is to run a given job even though TaskMan is not running on that node. These principals are applied by VPM to control the collection of performance data and manage the underlying DCL files.

To run from DCL, TaskMan requires the following:

- a. VMS Username: TASKMAN
- b. VMS Batch queues for each node in cluster named "TMS<nodename>"
- c. A VMS directory to hold a LOGIN.COM, ZTMWDCL.COM, and ZTMSWDCL.COM along with TaskMan-related log files and a system-wide logical name, "DHCP\$TASKMAN," defined on all nodes pointing to this directory.
- d. Box:Volume pairs and a DSM Environment Manager defined for all nodes in the cluster (TASKMAN SITE PARAMETERS file (#14.7)). Defining the DSM Environment, stopping and restarting TaskMan causes him to run from a DCL context. Deleting this entry, stopping and restarting TaskMan causes him to run in "normal" mode.

This task can be accomplished at any point prior to configuring and enabling VPM.

Alternatively, to assist with setting up the components needed by TaskMan *after* installing Toolkit V. 7.3, we have included the routine ^XUCMTM. To execute the routine, you should be logged in with the VMS privileges OPER and SYSPRV. Log into your DSM Production account and execute the routine from programmer mode. Again, this step must be completed *prior* to configuring and enabling VPM.

NOTE: For complete information on configuring TaskMan to run in a DCL context see the topic entitled "Running TaskMan with a VMS DCL Context" under the "Task Manager" chapter in the *Kernel Systems Manual V. 7.1* (pp. 294-298).

Sample Dialogue of Running ^XUCMTM

```
>D ^XUCMTM
This routine will assist you in configuring TASKMAN to run from a
DCL CONTEXT.
This procedure begins on page 294 of the Kernel 7.1 SYSTEMS MANUAL.

First, select an HFS device for writing to Taskman's home directory.
Select a HOST FILE SERVER device: HFS DISK FILE
HOST FILE NAME: TMP.TMP// <RET> INPUT/OUTPUT OPERATION: N

Now, let's create Taskman's home directory.
Enter the drive/path: USER$:[TASKMAN] (this entry is site specific)
This step creates a new entry in UAF called TASKMAN.
You will need to provide the UIC code in the format '[#,#]'.
Taskman will require at LEAST the following privileges:
CMKRNL, TMPMBX, OPER, NETMBX
Would you like to see a brief listing of UAF records? YES// NO
Assign TASKMAN to what UIC: [50,20] (this entry is site specific)
Would you like to copy an existing user over to TASKMAN? Y// NO

%UAF-I-ADDMSG, user record successfully added
%UAF-I-RDBADDMSGU, identifier TASKMAN value: [000050,000020] added to rights
data base
%CREATE-I-EXISTS, USER$:[TASKMAN] already exists

...WRITING OUT 'LOGIN.COM'
...WRITING OUT 'ZTMWDCL.COM'
...WRITING OUT 'ZTMSWDCL.COM'
The final step will be to define the TASKMAN batch queues for each node
in your cluster.
Enter the name of each node in your DHCP cluster. Press RETURN when finished.
Enter NODENAME: 612K01 (enter the nodenames at your site)
Enter NODENAME: 612K02
Enter NODENAME: <RET> (at this point, your queues have been created)
FINAL CHECKS:
1. Verify that you can log in as the user TASKMAN.
2. For each node that has the TM$ batch queue, define the system
   logical DHCP$TASKMAN=taskman's home directory. Be sure to place
   the command in your system startup procedure. (see page 295)
3. If you have implemented ACL security for your DSM environments
   log into your manager account and D ^ACL. Provide MANAGER access
   for the new user TASKMAN.
4. Using the option SITE PARAMETER EDIT, define a box-volume pair for
   each node containing the TM$NODENAME batch queue. Be sure to fill
   the field VAX/ALPHA DSM ENVIRONMENT FOR DCL.
5. STOP/RESTART TASKMAN TO ACTIVATE THE NEW SETTINGS.
```

Review the New VMS User, TASKMAN

```

KRN,KDE>
612K01: MC AUTHORIZE
UAF> SHO TASKMAN

Username: TASKMAN                               Owner:
Account:                                         UIC:   [50,20] ([DEV,TASKMAN])
CLI:      DCL                                   Tables: DCLTABLES
Default:  USER$:[TASKMAN]
LGICMD:   LOGIN.COM
Flags:    DisCtlY Restricted DisWelcome DisReport Captive
Primary days:  Mon Tue Wed Thu Fri
Secondary days:                               Sat Sun
No access restrictions
Expiration:      (none)      Pwdminimum:  6      Login Fails:      0
Pwdlifetime:    180 00:00      Pwdchange:      (pre-expired)
Last Login:      (none) (interactive),      (none) (non-interactive)
Maxjobs:         0      Fillm:      100  Byt1m:      40960
Maxacctjobs:     0      Shrfillm:     0  Pbyt1m:      0
Maxdetach:       0      B1O1m:      18  JTquota:     1024
Prclm:           2      D1O1m:      18  WSdef:       300
Prio:            4      AST1m:      24  WSquo:       500
Queprio:         0      TQE1m:      10  WSextent:    2048
CPU:             (none)  Enqlm:      300 Pgflquo:    10240
Authorized Privileges:
  CMKRNL TMPMBX OPER NETMBX
Default Privileges:
  CMKRNL TMPMBX OPER NETMBX
UAF> EXIT

```

NOTE: Password protect your new user and log in to test the password protection. If you do not use ACL protection on your MUMPS accounts, TaskMan may need to have SYSPRV privilege as well.

Grant the New User **TASKMAN** Manager Access to DSM

```
MGR,KDE>D ^ACL
```

```
Environment Access Utilities
```

- | | | |
|----|------------------------------|--------------|
| 1. | ADD/MODIFY USER | (ADD^ACL) |
| 2. | DELETE USER | (DELETE^ACL) |
| 3. | MODIFY ACTIVE AUTHORIZATIONS | (^ACLSET) |
| 4. | PRINT AUTHORIZED USERS | (PRINT^ACL) |

```
Select Option > 1. <RET> ADD/MODIFY USER
```

```
OpenVMS User Name: > TASKMAN
```

ACCESS MODE	VOL	UCI	ROUTINE
-----	---	---	-----

```
No access rights for this user.
```

```
Access Mode ([M]ANAGER, [P]ROGRAMMER, or [A]PPPLICATION): > M
```

USER	ACCESS MODE	VOL	UCI	ROUTINE
----	-----	---	---	-----

```
TASKMAN      MANAGER
```

```
OK to file? <Y> Y
```

```
Identifier DSM$MANAGER_KDAMGR granted to user TASKMAN.
Modifications have been made to the OpenVMS rights database.
These changes will take effect the next time TASKMAN logs in to
the OpenVMS system.
```

```
OpenVMS User Name: > <RET>
```

```
OK to activate changes now? <Y> Y
```

```
Creating access authorization file: DSA0:[KDAMGR]DSM$ACCESS.DAT.
                                     Press RETURN to continue
```

Verify that your Batch Queues were Created

```
612K01: SHO QUE/FULL TM$*
```

```
Batch queue TM$612K01, idle, on 612K01::  
  /BASE_PRIORITY=4 /JOB_LIMIT=50 /OWNER=[DEV,TASKMAN]  
  /PROTECTION=(S:E,O:D,G:R,W:W)
```

```
Batch queue TM$612K02, idle, on 612K02::  
  /BASE_PRIORITY=4 /JOB_LIMIT=50 /OWNER=[DEV,TASKMAN]  
  /PROTECTION=(S:E,O:D,G:R,W:W)
```

- Set up *two* new mail groups. The first should contain only local recipients for VAX/ALPHA Performance Monitor (VPM) messages and alerts. The second should contain the remote recipient, G.CMP@ISC-SF.VA.GOV. If your local ISC wishes to collect and file site data, enter an appropriate recipient for your local ISC as well. You are asked to enter these new mail groups in the CM SITE PARAMETERS file (#8986.095) at the conclusion of the Toolkit init.
- ISCs wishing to collect performance data from a site may request server routines from ISC-SF to file the data.

Verify an Entry Exists in the DEVICE file (#3.5) for the Following Devices:

NOTE: Some entries are site-specific.

NAME: HFS (<i>name optional</i>)	\$I: TMP.TMP
ASK DEVICE: YES	ASK PARAMETERS: NO
VOLUME SET(CPU): ISC	LOCATION OF TERMINAL: HOST DISK FILE
ASK HOST FILE: YES	ASK HFS I/O OPERATION: YES
MARGIN WIDTH: 132	FORM FEED: #
PAGE LENGTH: 64	BACK SPACE: \$C(8)
SUBTYPE: P-OTHER	TYPE: HOST FILE SERVER
NAME: SYS\$INPUT	\$I: SYS\$INPUT:.;
ASK DEVICE: NO	ASK PARAMETERS: NO
LOCATION OF TERMINAL: DISK FILE	MARGIN WIDTH: 80
FORM FEED: #	PAGE LENGTH: 64
BACK SPACE: \$C(8)	SUBTYPE: P-OTHER80
TYPE: TERMINAL	

MSM-PC Installations

MSM SITES should complete the following preliminary steps to enable performance monitoring:

1. Review the "Advance Preparation" topic in this manual for important information on Global Placement/Protection of the ^XT, ^XUCM, and ^XUCS globals.
2. On the Compute/Print Servers, in the Manager UCI, use ^%GDEL and delete the ^RTHIST global and reset it to ^RTHIST="".

This *only* needs to be done if the ^RTHIST global is pre V4 of MSM.

3. Prepare your other CPUs for support of TaskMan jobs. Move the following Kernel V. 7.1 and FileMan V. 20 routines to the Manager UCI of the File/Shadow Servers:

DIDT*
DIRCR
XUCIMSM
ZUA
ZT*
ZOS*

ZI*
-ZISL*
ZISLVR
ZISLDIS
ZISLSIT
ZISLPC

4. Setup the Global Translation on the File Server.

```
>D ^SYSGEN
      MSM - System Generation Utility
Select SYSGEN Option: 3 - Edit Configuration Parameters
Select Configuration <FSA>: FSA
Select SYSGEN Option: 13 - Translation/Replication Table Maintenance
Available Functions:
  1 - Edit Translation Table
  2 - Enable Translation
  3 - Disable Translation
  4 - Edit Replication Table
  5 - Translation Table List
  6 - Replication Table List
Select Option: 1 - Edit Translation Table
Translation table is empty.
Enter Translation Table Index: 1
Global name: %ZOSF
Collating sequence <NUMERIC>: NUMERIC
Global encoding [7=7-bit/8=8-bit] <8>: 8
UCI to translate from: MGR,FSA
```

4. Setup the Global Translation on the File Server (continued):

```

UCI to translate to: MGR,FSA
UCI for maintenance of locks <MGR,FSA>: MGR,FSA
Replication table index:
Enable translation <YES>: YES
Enable lock table translation <YES>: YES
Enter Translation Table Index: 2
Global name: %Z*
Collating sequence <NUMERIC>: NUMERIC
Global encoding [7=7-bit/8=8-bit] <8>: 8
UCI to translate from: MGR,FSA
UCI to translate to: MGR,PSA
UCI for maintenance of locks <MGR,PSA>: MGR,PSA
Replication table index:
Enable translation <YES>: YES
Enable lock table translation <YES>: YES
Enter Translation Table Index: ^L
Current Translation Table:

```

#	Global Name(s)	Translate From UCI	To UCI	Lock Master	Repl Ind	Functions Enabled	Coll Seq	Global encode
1*	%ZOSF	MGR,FSA	MGR,FSA	MGR,FSA		TRANSLATION LOCK MASTER	NUM	8-bit
2*	%Z*	MGR,FSA	MGR,PSA	MGR,PSA		TRANSLATION LOCK MASTER	NUM	8-bit

```

Entries with a '*' have been modified since Translation was enabled.
The Translation Table in memory does not reflect these changes.
Translation is not enabled
Enter Translation Table Index:
Press <RETURN> to continue
Available Functions:
  1 - Edit Translation Table
  2 - Enable Translation
  3 - Disable Translation
  4 - Edit Replication Table
  5 - Translation Table List
  6 - Replication Table List
Select Option: 2 - Enable Translation
Enabling translation...
Press <RETURN> to continue
Available Functions:
  1 - Edit Translation Table
  2 - Enable Translation
  3 - Disable Translation
  4 - Edit Replication Table
  5 - Translation Table List
  6 - Replication Table List
Select Option:

```

5. Run ZTMGRSET in the Manager's UCI of the File server.

6. In MGR, rename the following FileMan routines:

```
>ZL DIDT
>ZS %DT
>ZL DIDTC
>ZS %DTC
>ZL DIRCR
>ZS %RCR
```

7. Edit the File Servers for TASKMAN SITE PARAMETERS (#14.7), VOLUME SET (#14.5), and UCI ASSOCIATION (#14.6) files:

NOTE: For additional information on this, please refer to page 246 of the *Kernel Systems Manual V. 7.1*.

```
Task Manager
Select Task Manager Option: Taskman Management Utilities
Select Taskman Management Utilities Option: Edit Taskman Parameters
Select Edit Taskman Parameters Option: SITE Parameters Edit
Select TASKMAN SITE PARAMETERS BOX-VOLUME PAIR: FSB
  ARE YOU ADDING 'FSB' AS A NEW TASKMAN SITE PARAMETERS (THE 4TH)? Y (YES)
BOX-VOLUME PAIR: FSB//
LOG TASKS?: N NO
DEFAULT TASK PRIORITY: 4
TASK PARTITION SIZE:
SUBMANAGER RETENTION TIME: 0
TASKMAN JOB LIMIT: 14
TASKMAN HANG BETWEEN NEW JOBS: 1
MODE OF TASKMAN: COMPUTE SERVER <-----IMPORTANT!

NOTE: This setup differs to allow MPM to initiate and run tasks on your file
      servers.

VAX DSM ENVIRONMENT FOR DCL
OUT OF SERVICE: NO
LOAD BALANCE ROUTINE:
Select TASKMAN SITE PARAMETERS BOX-VOLUME PAIR:
Select Edit Taskman Parameters Option: VOLume Set Edit
Select VOLUME SET: FSB
  ARE YOU ADDING 'FSB' AS A NEW VOLUME SET (THE 5TH)? Y (YES)
VOLUME SET: FSB// <RET>
TYPE: COMPUTE SERVER
INHIBIT LOGONS?: N NO
LINK ACCESS?: <RET>
OUT OF SERVICE?: N NO
REQUIRED VOLUME SET?: N NO
TASKMAN FILES UCI: MGR
TASKMAN FILES VOLUME SET: PSA
REPLACEMENT VOLUME SET: <RET>
DAYS TO KEEP OLD TASKS: 4
Select VOLUME SET: <RET>
Select Edit Taskman Parameters Option: UCI Association Table Edit
```

7. Edit the File Servers for TASKMAN SITE PARAMETERS, VOLUME SET, and UCI ASSOCIATION files (continued):

```
Select UCI ASSOCIATION FROM UCI: VAH
  1  VAH      PSA
  2  VAH      CSA
  3  VAH      CSB
  4  VAH      FSA
CHOOSE 1-4:
ARE YOU ADDING 'VAH' AS A NEW UCI ASSOCIATION (THE 9TH)? Y (YES)
UCI ASSOCIATION NUMBER: 9// <RET>
UCI ASSOCIATION FROM VOLUME SET: FSB
UCI ASSOCIATION TO VOLUME SET: <RET>
UCI ASSOCIATION TO UCI: <RET>
FROM UCI: VAH// <RET>
FROM VOLUME SET: FSB// <RET>
TO VOLUME SET: <RET>
TO UCI:
Select UCI ASSOCIATION FROM UCI: MGR
  1  MGR      PSA
  2  MGR      CSA
  3  MGR      CSB
  4  MGR      FSA
CHOOSE 1-4:
ARE YOU ADDING 'MGR' AS A NEW UCI ASSOCIATION (THE 10TH)? Y (YES)
UCI ASSOCIATION NUMBER: 10// <RET>
UCI ASSOCIATION FROM VOLUME SET: FSB
UCI ASSOCIATION TO VOLUME SET: <RET>
UCI ASSOCIATION TO UCI: <RET>
FROM UCI: MGR// <RET>
FROM VOLUME SET: FSB// <RET>
TO VOLUME SET: <RET>
TO UCI: <RET>

Select UCI ASSOCIATION FROM UCI:
```

Begin the Installation

For VAX/ALPHA sites: Copy the contents of the media into a VMS file if you have not already done so. Later on in the installation process, the routines may then be read into production from disk which, for most configurations, is faster than reading from tape or floppy media. Also, create a large symbol table at sign-on, (\$DSM/SYM=100000) so there is enough space to work.

For MSM sites: Be sure to run the inits on the Print Server (e.g., Production account, not Manager account), where TaskMan resides, so that tasked post-inits run. Also, when logging on, increase the symbol table size to 24 so that there is enough space to work:

```
UCI,VOL:ROU:24
```

For other sites: Be sure to run the inits with as large a partition as you can.

- **Logon using the console.**

VAX/ALPHA sites: To maneuver without access restrictions, use a privileged VMS account.

MSM sites: log onto the print server.

<p>Begin the installation in the Production account (e.g., VAH)</p>
--

It is assumed that you have the capability to move back and forth from the Manager and Production accounts. After moving to another UCI, it is useful to verify your location as a safeguard (e.g., >W \$ZU(0) or use another technique).

- **In VAH: Logons are *not* inhibited.** Users may remain on the system during installation provided they are not running any options in the following menus:
 - [XUPROG] Programmer Options
 - [XUSITEMGR] Operations Management
- **VMS sites should unschedule the options, XUCM TASK VPM and XUCM TASK NIT for the duration of the installation.**
- **If files have been configured for version 7.2 of Multi-Term Look-Up, users of MTLU may experience errors while new ^XTLK* routines are being installed. Since installation time is brief and MTLU look-ups are infrequent, any inconvenience to users may be minimal. They should simply repeat their look-up at a later time.**

**Move over to the Manager (Library) account
(e.g., MGR)**

- **In MGR: Disable routine mapping** (if applicable) for Library and Production accounts.

DSM for OpenVMS

>D ^RMAP

MSM and M/SQL

Not Applicable

**Move back to the Production account
(e.g., VAH)**

Read the Routines into Production

- **In VAH: Read Routines into Production.** Load routines from the tape or, for VAX/ALPHA sites, from the VMS file created earlier from the tape.

(It is assumed that you are familiar with your operating system utilities for loading, saving, and restoring routines.)

M/SQL

```
>D ^%RI
```

ALL OTHER SYSTEMS

```
>D ^%RR
```

- **In VAH: Optionally run the NTEG routines in the Production account** if you have not already done so in a test account. Report any "off-by" results to your local ISC. Discrepancies may simply indicate that your tape includes patched routines.

```
>D ^XTNTEG
```

Example of Routine Restore done at the San Francisco ISC

```
KRN,KDE>D ^%RR
```

```
Routine Restore
```

```
Input Device ? > KTK7_3.RTN
```

```
Restoring routines from USER$:[KERNEL.TK73BLD]KTK7_3.RTN;1
```

```
Saved by %RS from [NXT,KDE] on 3-APR-1995 12:00:53.50
```

```
Header: Kernel Toolkit 7.3 created by JIC at ISC-SF
```

```
Restore All (A), Selected (S), or Confirm on overwrite (C) ? <A> <RET>
```

XDRCNT	XDRDADD	XDRDADJ	XDRDCOMP	XDRDFPD	XDRDLIST	XDRDMAIN	XDRDOC
XDRDOC1	XDRDOC2	XDRDPDTI	XDRDPRGE	XDRDQUE	XDRDSCOR	XDRDSTAT	XDRDUP
XDREMSG	XDRERR	XDRHLP	XDRMADD	XDRMAIN	XDRMAINI	XDRMPACK	XDRMRG
XDRMRG1	XDRMSG	XDRMVFY	XDRPREI	XDRU1	XINDEX	XINDEX1	XINDEX10
XINDEX11	XINDEX2	XINDEX3	XINDEX4	XINDEX5	XINDEX51	XINDEX52	XINDEX53
XINDEX6	XINDEX7	XINDEX8	XINDEX9	XTBASE	XTCMFILN	XTEDTVXD	XTFC0
XTFC1	XTFCE	XTFCE1	XTFCR	XTFCR1	XTINEND	XTINI001	XTINI002
XTINI003	XTINI004	XTINI005	XTINI006	XTINI007	XTINI008	XTINI009	XTINI00A
XTINI00B	XTINI00C	XTINI00D	XTINI00E	XTINI00F	XTINI00G	XTINI00H	XTINI00I
XTINI00J	XTINI00K	XTINI00L	XTINI00M	XTINI00N	XTINI00O	XTINI00P	XTINI00Q
XTINI00R	XTINI00S	XTINI00T	XTINI00U	XTINI00V	XTINI00W	XTINI00X	XTINI00Y
XTINI00Z	XTINI010	XTINI011	XTINI012	XTINI013	XTINI014	XTINI015	XTINI016
XTINI017	XTINI018	XTINI019	XTINI01A	XTINI01B	XTINI01C	XTINI01D	XTINI01E
XTINI01F	XTINI01G	XTINI01H	XTINI01I	XTINI01J	XTINI01K	XTINI01L	XTINI01M
XTINI01N	XTINI01O	XTINI01P	XTINI01Q	XTINI01R	XTINI01S	XTINI01T	XTINI01U
XTINI01V	XTINI01W	XTINI01X	XTINI01Y	XTINI01Z	XTINI020	XTINI021	XTINI022
XTINI023	XTINI024	XTINI025	XTINI026	XTINI027	XTINI028	XTINI029	XTINI02A
XTINI02B	XTINI02C	XTINI02D	XTINI02E	XTINI02F	XTINIS	XTINIT	XTINIT1
XTINIT2	XTINIT3	XTINIT4	XTINIT5	XTINITY	XTINOK	XTKERM1	XTKERM2
XTKERM3	XTKERM4	XTKERMIT	XTLATSET	XTLKDICL	XTLKEFOP	XTLKKSCH	XTLKKWL
XTLKKWL1	XTLKKWL2	XTLKKWLD	XTLKMGR	XTLKPRT	XTLKPST	XTLKTICD	XTLKTOKN
XTLKWIC	XTNTEG	XTNTEG0	XTNTEG01	XTRCMP	XTRGRPE	XTRTHV	XTSPING
XTSUMBLD	XTVCHG	XTVGC1	XTVGC1A	XTVGC2	XTVGC2A	XTVGC2A1	XTVNUM
XTVRC1	XTVRC1A	XTVRC1Z	XTVRC2	XTVRCRES	XUCIN001	XUCIN002	XUCIN003
XUCIN004	XUCIN005	XUCIN006	XUCIN007	XUCIN008	XUCIN009	XUCIN00A	XUCIN00B
XUCIN00C	XUCIN00D	XUCIN00E	XUCIN00F	XUCIN00G	XUCIN00H	XUCIN00I	XUCIN00J
XUCIN00K	XUCIN00L	XUCIN00M	XUCIN00N	XUCIN00O	XUCIN00P	XUCIN00Q	XUCIN00R
XUCIN00S	XUCIN00T	XUCIN00U	XUCIN00V	XUCIN00W	XUCIN00X	XUCIN00Y	XUCIN00Z
XUCIN010	XUCIN011	XUCINIS	XUCINIT	XUCINIT1	XUCINIT2	XUCINIT3	XUCINIT4
XUCINIT5	XUCMBR1	XUCMBR2	XUCMBR3	XUCMBRTL	XUCMDSL	XUCMFGI	XUCMFIL
XUCMGRAF	XUCMNI2A	XUCMNIT	XUCMNIT1	XUCMNIT2	XUCMNIT3	XUCMNIT4	XUCMNIT5
XUCMNT3A	XUCMPA	XUCMPA1	XUCMPA2	XUCMPA2A	XUCMPA2B	XUCMPOST	XUCMPRE
XUCMTM	XUCMTM1	XUCMVP	XUCMVP1	XUCMVPI	XUCMVP	XUCMVP1	XUCMVPS
XUCMVP	XUCPCLCT	XUCPFRMT	XUCPRAW	XUCS1E	XUCS1R	XUCS1RA	XUCS1RB
XUCS1RBA	XUCS2E	XUCS2R	XUCS2RA	XUCS2RB	XUCS2RBA	XUCS4E	XUCS4R

Example of Routine Restore done at the San Francisco ISC (continued):

XUCS4RB	XUCS5E	XUCS5EA	XUCS6E	XUCS6R	XUCS8E	XUCS8R	XUCS8RB
XUCS8RG	XUCS8RGA	XUCSCDE	XUCSCDG	XUCSCDGA	XUCSCDR	XUCSCDRB	XUCSI001
XUCSI002	XUCSI003	XUCSI004	XUCSI005	XUCSI006	XUCSI007	XUCSI008	XUCSI009
XUCSI00A	XUCSI00B	XUCSI00C	XUCSI00D	XUCSI00E	XUCSI00F	XUCSI00G	XUCSI00H
XUCSI00I	XUCSI00J	XUCSI00K	XUCSI00L	XUCSINI1	XUCSINI2	XUCSINI3	XUCSINI4
XUCSINI5	XUCSINIS	XUCSINIT	XUCSLOAD	XUCSPRG	XUCSRV	XUCSTM	XUCSTME
XUCSUTL	XUCSUTL2	XUCSUTL3	XURTL	XURTL1	XURTL2	XURTL3	XURTL4
XURTLC	XURTLK	ZINDEX	ZINDEX1	ZINDEX10	ZINDEX11	ZINDEX2	ZINDEX3
ZINDEX4	ZINDEX5	ZINDEX51	ZINDEX52	ZINDEX53	ZINDEX6	ZINDEX8	ZINDEX9
ZINDEXH	ZTEDIT	ZTEDIT1	ZTEDIT2	ZTEDIT3	ZTEDIT4	ZTGS	ZTP1
ZTPP	ZTRDEL	ZTRTHV					
363 routines restored							

**Continue working in the Production account
(e.g., VAH)**

Move Routines to the Manager Account

- **In VAH: Move routines out to a host file.**

M/SQL

```
>D ^%RO
```

ALL OTHER SYSTEMS

```
>D ^%RS (or use ^%RCOPY)
```

Example of Routine Save done at the San Francisco ISC

```
NXT,KDE>D ^%RS
```

Routine Save

Output Device ? > **TKMGR.RTN**

Header comment...

```
routine(s) ? > ZT*
searching directory ...
routine(s) ? > -ZTM*
routine(s) ? > -ZTL*
routine(s) ? > -ZTER*
routine(s) ? > ZOS*
searching directory ...
routine(s) ? > ZIND*
searching directory ...
routine(s) ? > ZTMGRSET
routine(s) ? > <RET>
```

Saving routines on USER\$:[BETA]TKMGR.RTN;3

ZINDEX	ZINDEX1	ZINDEX10	ZINDEX11	ZINDEX2	ZINDEX3	ZINDEX4	ZINDEX5
ZINDEX51	ZINDEX52	ZINDEX53	ZINDEX6	ZINDEX8	ZINDEX9	ZINDEXH	ZOSFDTM
ZOSFGTM	ZOSFM11P	ZOSFMSM	ZOSFMVX	ZOSFVXD	ZOSV1DTM	ZOSV1GTM	ZOSV1VXD
ZOSV2MSM	ZOSV2VXD	ZOSVDTM	ZOSVGTM	ZOSVM11P	ZOSVMSM	ZOSVMVX	ZOSVVXD
ZTBKC	ZTBKCDSM	ZTBKCDTM	ZTBKCOMP	ZTBKCMSM	ZTBKCMVX	ZTBKCVXD	ZTEDIT
ZTEDIT1	ZTEDIT2	ZTEDIT3	ZTEDIT4	ZTGS	ZTMGRSET	ZTP1	ZTPP
ZTRDEL	ZTRTHV						

50 routines saved

**Move over to the Manager (Library) account
(e.g., MGR)**

- **In MGR: Restore routines from the host file to your MGR account.**

M/SQL

>D ^%RI

ALL OTHER SYSTEMS

>D ^%RR

Run the Manager Setup Routine

- **In MGR: Run the Manager Setup Routine.**

Run this routine so that operating system-specific routines can be identified and renamed as "% routines for proper functioning in the Manager account. After responding to the prompts as illustrated on the following page, ZTMGRSET loads the routines which are common to all systems and saves them as percent routines (e.g., ZINDEX is saved as %INDEX). It then installs the ^%Z editor and checks that ^%ZIS("C") only holds a call to the ^%ZISC routine. Finally, it sets up two files stored in ^%ZUA, the FAILED ACCESS ATTEMPT LOG (#3.05) and the PROGRAMMER MODE LOG (#3.07) files.

Enter the name of the MUMPS implementation you are running. This sets the first piece of ^%ZOSF("OS").

Indicate the name of your Manager account.

Indicate the name of your sign-on Production account.

Enter the name of the current volume or directory set. Notice that ^ZTMGRSET no longer asks you about the location of the ^XMB global. Instead, it deletes the obsolete ^%ZOSF("MASTER") and ^%ZOSF("SIGNOFF") nodes.

```
>D TOOLKIT^ZTMGRSET
```

DSM for OpenVMS

```
SYSTEM:    VAX DSM(V6)
NAME OF MANAGER'S UCI:  MGR,ROU
PRODUCTION (SIGN-ON) UCI:  VAH,ROU
NAME OF VOLUME SET:    ROU
```

MSM

```
SYSTEM:    MSM
NAME OF MANAGER'S UCI:  MGR,PSA
PRODUCTION (SIGN-ON) UCI:  VAH,PSA
NAME OF VOLUME SET:    PSA
```

If you haven't already done so, then at this point you may load the Toolkit Manager account routines (Z) from disk to all other CPU/volume groups for performance monitoring. Be sure to run TOOLKIT^ZTMGRSET in the MGR UCI of each CPU.*

M/SQL

```
SYSTEM:    M/SQL
NAME OF MANAGER'S UCI:  MG,BLUE
PRODUCTION (SIGN-ON) UCI:  VA,BLUE
NAME OF VOLUME SET:    BLUE
```

**Continue working in the Manager (Library) account
(e.g., MGR)**

Example of Manager Setup Routine done at the San Francisco ISC

```
>D TOOLKIT^ZTMGRSET
```

```
ZTMGRSET Version 7.3
```

```
HELLO! I exist to assist you in correctly initializing the MGR account  
or to update the current account.
```

```
I think you are using VAX DSM(V6)
```

```
Which MUMPS system should I install?
```

```
1 = NOT SUPPORTED
```

```
2 = M/SQL-PDP
```

```
3 = M/SQL-VAX
```

```
4 = DSM V4.1
```

```
5 = VAX DSM(V6)
```

```
6 = MSM
```

```
7 = Datatree
```

```
System: 5// <RET>
```

```
Removing obsolete ^%ZOSF nodes...
```

```
I will now rename a group of routines specific to your operating system.
```

```
Loading ZOSVVXD      Saved as %ZOSV
```

```
Loading ZTBKC        Saved as %ZTBKC
```

```
Loading ZTBKCVXD     Saved as %ZTBKC1
```

```
Loading ZOSV1VXD     Saved as %ZOSV1
```

```
Loading ZOSV2VXD     Saved as %ZOSV2
```

```
NAME OF MANAGER'S UCI,VOLUME SET: MGR,KDE// <RET>
```

```
PRODUCTION (SIGN-ON) UCI,VOLUME SET: KRN,KDE// <RET>
```

```
NAME OF VOLUME SET: KDE// <RET>
```

Example of Manager Setup Routine done at the San Francisco ISC (continued):

```
Now to load routines common to all systems.  
Loaded ZINDEX          Saved as %INDEX  
Loaded ZINDX1          Saved as %INDX1  
Loaded ZINDX10         Saved as %INDX10  
Loaded ZINDX11         Saved as %INDX11  
Loaded ZINDX2          Saved as %INDX2  
Loaded ZINDX3          Saved as %INDX3  
Loaded ZINDX4          Saved as %INDX4  
Loaded ZINDX5          Saved as %INDX5  
Loaded ZINDX51         Saved as %INDX51  
Loaded ZINDX52         Saved as %INDX52  
Loaded ZINDX53         Saved as %INDX53  
Loaded ZINDX6          Saved as %INDX6  
Loaded ZINDX8          Saved as %INDX8  
Loaded ZINDX9          Saved as %INDX9  
Loading ZTPP           Saved as %ZTPP  
Loading ZTP1           Saved as %ZTP1  
Loading ZTRDEL         Saved as %ZTRDEL  
Installing ^%Z editor  
ALL DONE
```

**Continue working in the Manager (Library) account
(e.g., MGR)**

Review Global Protection for ^%ZRTL

- **In MGR:** Confirm that the ^%ZRTL global is defined in the Manager account and set with appropriate protections. (The ^%ZRTL global holds response time monitors.)

^%ZRTL is common to all processors.

DSM for OpenVMS

```
>D ^%GLOMAN

(Manage globals in which UCI?: MGR)

^%ZRTL
System) RWP   World) RW   Group) RW   UCI) RWP
```

MSM

```
>D ^%GCH

(Set protection)

^%ZRTL
System) RWD   World) RWD   Group) RWD USER) RWD
```

M/SQL

```
>D ^%PROTECT

(Manage globals in which UCI?: MGR)

^%ZRTL
Network) RWD World) RW   Group) RW   Owner) RWD
```

Establish Global Translation

- **In MGR:** Review translation for ^XT and ^XUCM on DSM systems, ^XT and ^XUCS on MSM systems.

DSM for OpenVMS

```
>D ^TRANTAB (for DSM V4.0 or later)
```

(Be sure that ^XT and ^XUCM are translated to a cluster mounted volume set.)

MSM

```
>D ^TRANSLAT
```

(Be sure that ^XT and ^XUCS are translated across VAH UCIs.)

M/SQL

Not Applicable

**Move back to the Production account
(e.g., VAH)**

Do the First Part of the Installation

- **In VAH: Run the Toolkit inits.**

For DSM for OpenVMS: Create a large symbol table at sign-on, (\$ DSM/UCI=VAH/SYM=100000).

For MSM: Increase the symbol table size to 24 by responding to the UCI prompt as follows:
UCI,VOL:ROU:24. Otherwise, type D ^%PARTSIZ to set the partition size.

For M/SQL: Be sure you have at least a 16K partition. W \$S to see the current size.

ALL OPERATING SYSTEMS

```
>D ^XUP (To set DUZ when
        responding to the Access Code
        prompt. Press return at the
        OPTION prompt.)
```

```
>D Q^DI (To set DUZ(0)="@" .
        Press return at the OPTION
        prompt.)
```

XTINITs take approximately 7-15 minutes.

If you have multiple CPUs, turn to the topic "On the Other Toolkit V. 7.2 CPUs (MSM and M/SQL)".

NOTE: The text of the init dialogue may not be an exact match of what you see when running the installation. It is provided as a best approximation of a typical install. Explanatory notes are provided along with the dialogue that should give some indication why your experience may differ from the example presented here.

**From the Production account
(e.g., VAH)**

Example of an Init Done at the San Francisco ISC

NOTE: This is an example of an installation from the San Francisco development account. The messages at your site may look slightly different.

```
VAH,MTL>D ^XTINIT
```

```
This version (#7.3) of 'XTINIT' was created on 03-APR-1995
      (at NXT, by VA FileMan V.20.0)
```

```
I HAVE TO RUN AN ENVIRONMENT CHECK ROUTINE.
I'm checking to see if it is OK to install Toolkit v7.3
in this account.
```

```
Everything looks OK, Lets continue.
```

```
I AM GOING TO SET UP THE FOLLOWING FILES:
```

```
3.091      RESPONSE TIME
```

```
Note: You already have the 'RESPONSE TIME' File.
Shall I write over the existing Data Definition? YES// <RET>
```

```
3.092      RT DATE_UCI,VOL
```

```
Note: You already have the 'RT DATE_UCI,VOL' File.
Shall I write over the existing Data Definition? YES// <RET>
```

```
3.094      RT RAWDATA
```

```
Note: You already have the 'RT RAWDATA' File.
Shall I write over the existing Data Definition? YES// <RET>
```

```
15         DUPLICATE RECORD
```

```
Note: You already have the 'DUPLICATE RECORD' File.
```

```
15.1       DUPLICATE RESOLUTION
```

```
Note: You already have the 'DUPLICATE RESOLUTION' File.
```

```
8980       KERMIT HOLDING
```

```
Note: You already have the 'KERMIT HOLDING' File.
Shall I write over the existing Data Definition? YES// <RET>
```

```
8984.1     LOCAL KEYWORD
```

```
Note: You already have the 'LOCAL KEYWORD' File.
Shall I write over the existing Data Definition? YES// <RET>
```

Example of an Init Done at the San Francisco ISC (continued):

```
8984.2      LOCAL SHORTCUT
Note:  You already have the 'LOCAL SHORTCUT' File.
Shall I write over the existing Data Definition? YES// <RET>

8984.3      LOCAL SYNONYM
Note:  You already have the 'LOCAL SYNONYM' File.
Shall I write over the existing Data Definition? YES// <RET>

8984.4      LOCAL LOOKUP
Note:  You already have the 'LOCAL LOOKUP' File.
Shall I write over the existing Data Definition? YES// <RET>

8991        XTV ROUTINE CHANGES
Note:  You already have the 'XTV ROUTINE CHANGES' File.
Shall I write over the existing Data Definition? YES// <RET>

8991.19     XTV VERIFICATION PACKAGE
Note:  You already have the 'XTV VERIFICATION PACKAGE' File.
Shall I write over the existing Data Definition? YES// <RET>

8991.2      XTV GLOBAL CHANGES
Note:  You already have the 'XTV GLOBAL CHANGES' File.
Shall I write over the existing Data Definition? YES// <RET>

SHALL I WRITE OVER FILE SECURITY CODES? NO// Y <RET> (YES)
NOTE: This package also contains BULLETINS
      SHALL I WRITE OVER EXISTING BULLETINS OF THE SAME NAME? YES// <RET>
(YES)
NOTE: This package also contains SORT TEMPLATES
      SHALL I WRITE OVER EXISTING SORT TEMPLATES OF THE SAME NAME? YES// <RET>
(YES)
NOTE: This package also contains INPUT TEMPLATES
      SHALL I WRITE OVER EXISTING INPUT TEMPLATES OF THE SAME NAME? YES//
<RET> (YES)
NOTE: This package also contains PRINT TEMPLATES
      SHALL I WRITE OVER EXISTING PRINT TEMPLATES OF THE SAME NAME? YES//
<RET> (YES)
NOTE: This package also contains FUNCTIONS
      SHALL I WRITE OVER EXISTING FUNCTIONS OF THE SAME NAME? YES// <RET> (YES)
NOTE: This package also contains HELP FRAMES
      SHALL I WRITE OVER EXISTING HELP FRAMES OF THE SAME NAME? YES// <RET>
(YES)
NOTE: This package also contains SECURITY KEYS
      SHALL I WRITE OVER EXISTING SECURITY KEYS OF THE SAME NAME? YES// <RET>
(YES)
NOTE: This package also contains OPTIONS
      SHALL I WRITE OVER EXISTING OPTIONS OF THE SAME NAME? YES// <RET> (YES)

ARE YOU SURE EVERYTHING'S OK? NO// Y <RET> (YES)
```

Example of an Init Done at the San Francisco ISC (continued):

```

...HMMM, LET ME THINK ABOUT THAT A
MOMENT.....
.
.....
.
.
.....
'XDR ADD VERIFIED' Help Frame filed.
'XDR AUTO MERGE' Help Frame filed.
'XDR CHECK PAIR' Help Frame filed.
'XDR DUP ALGORITHM' Help Frame filed.
'XDR DUP RESOLUTION FILE CONT' Help Frame filed.
'XDR DUPLICATE RECORD LISTINGS' Help Frame filed.
'XDR DUPLICATE RESOLUTION FILE' Help Frame filed.
'XDR EDIT DUP RESOLUTION FILE' Help Frame filed.
'XDR IDENTIFY' Help Frame filed.
'XDR IDENTIFY CONTINUE' Help Frame filed.
'XDR IDENTIFY METHODS' Help Frame filed.
'XDR MERGE PROCESS' Help Frame filed.
'XDR MERGE SELECTED PAIR' Help Frame filed.
'XDR MERGE VERIFIED DUPLICATES' Help Frame filed.
'XDR PRINTLIST' Help Frame filed.
'XDR PURGE' Help Frame filed.
'XDR VERIFY ALL' Help Frame filed.
'XDR VERIFY SELECTED PAIR' Help Frame filed.
'XURTL RESPONSE TIME LOG' Help Frame filed....
'XDR ERROR' BULLETIN FILED -- Remember to add mail groups for new bulletins.
'XDR MERGED' BULLETIN FILED -- Remember to add mail groups for new bulletins.
'XDR VERIFIED' BULLETIN FILED -- Remember to add mail groups for new
bulletins.
.
.....
.
.
.
.
'XDR ADD VERIFIED DUPS' Option Filed
'XDR AUTO MERGE' Option Filed
'XDR CHECK PAIR' Option Filed
'XDR DISPLAY SEARCH STATUS' Option Filed
'XDR EDIT DUP RECORD STATUS' Option Filed
'XDR EDIT DUP RESOLUTION FILE' Option Filed
'XDR FIND POTENTIAL DUPLICATES' Option Filed
'XDR MAIN MENU' Option Filed
'XDR MANAGER UTILITIES' Option Filed
'XDR MERGE READY DUPLICATES' Option Filed
'XDR MERGE SELECTED PAIR' Option Filed
'XDR OPERATIONS MENU' Option Filed
'XDR PRINT LIST' Option Filed
'XDR PURGE' Option Filed
'XDR SEARCH ALL' Option Filed
'XDR TALLY STATUS FIELDS' Option Filed

```

Example of an Init Done at the San Francisco ISC (continued):

```
'XDR UTILITIES MENU' Option Filed
'XDR VERIFY ALL' Option Filed
'XDR VERIFY SELECTED PAIR' Option Filed
'XDR VIEW DUPLICATE RECORD' Option Filed
'XT-KERMIT EDIT' Option Filed
'XT-KERMIT MENU' Option Filed
'XT-KERMIT RECEIVE' Option Filed
'XT-KERMIT SEND' Option Filed
'XT-NUMBER BASE CHANGER' Option Filed
'XT-OPTION TEST' Option Filed
'XT-ROUTINE COMPARE' Option Filed
'XT-VARIABLE CHANGER' Option Filed
'XT-VERSION NUMBER' Option Filed
'XTCM DISK2MAIL' Option Filed
'XTCM MAIN' Option Filed
'XTFCE' Option Filed
'XTFCR' Option Filed
'XTLKLKUP' Option Filed
'XTLKMODKY' Option Filed
'XTLKMODPARK' Option Filed
'XTLKMODPARS' Option Filed
'XTLKMODSH' Option Filed
'XTLKMODSY' Option Filed
'XTLKMODUTL' Option Filed
'XTLKPRTUTL' Option Filed
'XTLKUSER2' Option Filed
'XTLKUTILITIES' Option Filed
'XTMENU' Option Filed
'XTMOVE' Option Filed
'XTMOVE-IN' Option Filed
'XTOOLS' Option Filed
'XTQUEUEABLE OPTIONS' Option Filed
'XTRDEL' Option Filed
'XTRGRPE' Option Filed
'XTSUMBLD' Option Filed
'XTSUMBLD-CHECK' Option Filed
'XTV EDIT VERIF PACKAGE' Option Filed
'XTV MENU' Option Filed
'XTVG COMPARE' Option Filed
'XTVG UPDATE' Option Filed
'XTVR COMPARE' Option Filed
'XTVR MENU' Option Filed
'XTVR MOST RECENT CHANGE DATE' Option Filed
'XTVR RESTORE PREV ROUTINE' Option Filed
'XTVR UPDATE' Option Filed
'XU FIRST LINE PRINT' Option Filed
'XUINDEX' Option Filed
'XUINDEX2' Option Filed
'XUPR RTN EDIT' Option Filed
'XUPR-ROUTINE-TOOLS' Option Filed
'XUPR-RTN-TAPE-CMP' Option Filed
```

Example of an Init Done at the San Francisco ISC (continued):

```
'XUPRGL' Option Filed
'XUPRROU' Option Filed
'XUROUTINE IN' Option Filed
'XUROUTINE OUT' Option Filed
'XUROUTINES' Option Filed
'XURTL' Option Filed
'XURTLC' Option Filed
'XURTLCK' Option Filed
'XURTLK' Option Filed
'XURTLM' Option Filed
'XURTLMA' Option Filed
'XURTLPL' Option Filed
'XURTLPG' Option Filed
'XURTLPL' Option Filed.....
NOTE THAT FILE SECURITY-CODE PROTECTION HAS BEEN MADE
```


Installing/Configuring the VAX/Alpha Performance Monitor (VPM)

NOTE: At this point, VAX/Alpha Sites only see the following (MSM sites may skip this portion of the dialogue):

```
Will now install the VAX/Alpha Performance Monitor (VPM)

This version (#7.3) of 'XUCINIT' was created on 03-APR-1995
    (at NXT, by VA FileMan V.20.0)

I AM GOING TO SET UP THE FOLLOWING FILES:

    8986.095  CM SITE PARAMETERS
Note:  You already have the 'CM SITE PARAMETERS' File.

    8986.098  CM BERNSTEIN DATA
Note:  You already have the 'CM BERNSTEIN DATA' File.

    8986.3    CM SITE NODENAMES
Note:  You already have the 'CM SITE NODENAMES' File.

    8986.35   CM SITE DISKDRIVES
Note:  You already have the 'CM SITE DISKDRIVES' File.

    8986.4    CM METRICS  (including data)
Note:  You already have the 'CM METRICS' File.
I will OVERWRITE your data with mine.

    8986.5    CM DISK DRIVE RAW DATA
Note:  You already have the 'CM DISK DRIVE RAW DATA' File.

    8986.51   CM NODENAME RAW DATA
Note:  You already have the 'CM NODENAME RAW DATA' File.

    8986.6    CM DAILY STATISTICS
Note:  You already have the 'CM DAILY STATISTICS' File.

SHALL I WRITE OVER FILE SECURITY CODES? NO// Y <RET> (YES)
NOTE: This package also contains BULLETINS
    SHALL I WRITE OVER EXISTING BULLETINS OF THE SAME NAME? YES// <RET>
(YES)
NOTE: This package also contains SORT TEMPLATES
    SHALL I WRITE OVER EXISTING SORT TEMPLATES OF THE SAME NAME? YES// <RET>
(YES)
NOTE: This package also contains INPUT TEMPLATES
    SHALL I WRITE OVER EXISTING INPUT TEMPLATES OF THE SAME NAME? YES//
<RET> (YES)
NOTE: This package also contains PRINT TEMPLATES
    SHALL I WRITE OVER EXISTING PRINT TEMPLATES OF THE SAME NAME? YES//
<RET> (YES)
```

Installing/Configuring the VPM (continued):

```
NOTE: This package also contains OPTIONS
      SHALL I WRITE OVER EXISTING OPTIONS OF THE SAME NAME? YES// <RET> (YES)

ARE YOU SURE EVERYTHING'S OK? NO// Y <RET> (YES)
Starting pre-init...
The ^XUCM global will now be synchronized with VPM file numbers

8986.095...DONE
8986.098...DONE
8986.3...DONE
8986.35...DONE
8986.4...DONE
8986.5...DONE
8986.51...DONE
8986.6...DONE

...HMMM, LET ME THINK ABOUT THAT A
MOMENT.....
.
.....
'XUCMBRTL' BULLETIN FILED -- Remember to add mail groups for new
bulletins.....
.
.....
'XUCM ANALYSE' Option Filed
'XUCM COMPUTE LOCAL REFERENCES' Option Filed
'XUCM DISK' Option Filed
'XUCM DISK RAW' Option Filed
'XUCM DSK IO' Option Filed
'XUCM DSK QUE' Option Filed
'XUCM EDIT DISK THRESHOLD' Option Filed
'XUCM EDIT REF THRESH' Option Filed
'XUCM EDIT VOL SET THRESH' Option Filed
'XUCM GRAF DSK IO' Option Filed
'XUCM GRAF DSK QUE' Option Filed
'XUCM GRAF MET AVE' Option Filed
'XUCM LIST DAILY STATS' Option Filed
'XUCM LIST RAW' Option Filed
'XUCM LIST VOL SET INFO' Option Filed
'XUCM LOCKS' Option Filed
'XUCM MAIN' Option Filed
'XUCM MODES' Option Filed
'XUCM ON/OFF' Option Filed
'XUCM PA' Option Filed
'XUCM PAGE' Option Filed
'XUCM PERFORMANCE MONITOR' Option Filed
'XUCM PURGE' Option Filed
'XUCM RAW RTHIST DATA' Option Filed
'XUCM REPORTS' Option Filed
```

Installing/Configuring the VPM (continued):

```
'XUCM SERVER' Option Filed
'XUCM SET ALERTS' Option Filed
'XUCM SETUP' Option Filed
'XUCM TASK MAIN' Option Filed
'XUCM TASK NIT' Option Filed
'XUCM TASK VPM' Option Filed
'XUCMBR MENU' Option Filed
'XUCMBR2' Option Filed
'XUCMBR2A' Option Filed
'XUCMBR2B' Option Filed
'XUCMBR2C' Option Filed
'XUCPFORMATTED' Option Filed
'XUCPKILL' Option Filed
'XUCPMENU' Option Filed
'XUCPRAWPRINT' Option Filed
'XUCPSORT' Option Filed
'XUCPTOGGLE' Option Filed.....
NOTE THAT FILE SECURITY-CODE PROTECTION HAS BEEN MADE
```

The CM METRICS file (#8986.4) is shipped with data. The metric names should not be modified.

The post-init allows you to configure the performance monitor for alpha systems.

Do not attempt to configure VPM at this point if you have not yet set up TaskMan to run in DCL mode. The option, Setup Performance Monitor allows you to configure VPM later.

```
<<BEGINNING VPM POST-INIT>>
This post-init will allow you to review and update your
VPM site file entries. Taskman will also install new VMS com files
in your VPM host directory.

TASKMAN MUST BE RUNNING FROM A DCL CONTEXT TO COMPLETE THIS STEP.
YOU CAN '^' OUT NOW IF THIS IS NOT THE CASE.

Note that VPM also requires a HFS device, SYS$INPUT, and XUCM RESOURCE.
IF YOU EXIT NOW, RUN THE OPTION, 'SETUP PERFORMANCE MONITOR'
LATER.

The routine ^XUCMTM was written to assist with setting up Taskman
to run from DCL. Make sure you have SYSPRV and OPER before attempting
to run this routine.
This routine allows you to define the site file parameters
needed to run VPM, then instructs taskman to create the
host system directories for data files and system-specific
command procedures.
```

Installing/Configuring the VPM (continued):

Select CM SITE PARAMETERS:

ANSWER WITH CM SITE PARAMETERS:

ISC SAN FRANCISCO

YOU MAY ENTER A NEW CM SITE PARAMETERS, IF YOU WISH

ANSWER WITH INSTITUTION NAME

Select CM SITE PARAMETERS: **ISC SAN FRANCISCO** CALIFORNIA 16000

...OK? YES// <RET> (YES)

SITE: ISC SAN FRANCISCO// <RET>

CMP HOST FILE PATH: USER\$:[CMP]// <RET>

MONITOR ENABLED/DISABLED: ENABLED// <RET>

HFS DEVICE: HFS// <RET>

DAYS TO KEEP RAW DATA: 90// <RET>

DAYS FOR COMPUTING REFERENCES: ??

This field is used to control your local reference mean and standard deviation. For example, if 90 is entered, then each evening your reference range will be re-computed based on the previous 90 days. This 90-day moving average is maintained by hardware-type in the CM METRICS file. In this scenario, current data will always be compared with the last 90 days, regardless of how well the system performed during that period. If this field is blank, no updating will occur. If you enter '999', ALL data will be used. Suggested usage: If your system appears to be functioning normally, enter 999 to include all data until the standard deviation appears to be stable and you are within 2 standard deviations of the VA reference mean. After a reasonable period of monitoring, set this field to null to 'fix' your reference ranges on a period that you consider 'normal' for that hardware. Your local standard deviation should be considerably smaller than those published by the VA and should be particularly useful for monitoring the affect of tuning or capacity changes.

DAYS FOR COMPUTING REFERENCES: **999**

MAILGROUP FOR REPORTS/ALERTS: VPM// <RET>

MAILGROUP FOR REMOTE XMITS: VPM// <RET>

DAYS TO KEEP DAILY AVERAGES: 999// <RET>

DAYS TO KEEP BRTL DATA: 365// <RET>

THRESHOLD (%) DSM BLOCKS FREE: 5// ??

This field will be referenced each evening to determine if there is sufficient space remaining in your volume sets. If the PERCENTAGE of DSM blocks free drops below this threshold for a VOLUME SET an alert will be fired.

THRESHOLD (%) DSM BLOCKS FREE: 5// <RET>

CONFIGURATION: LAVC// <RET>

CRT's IN SERVICE: 3// <RET>

PRINTERS IN SERVICE: 15// <RET>

NETWORKED WORKSTATIONS: 38// <RET>

STANDALONE WORKSTATIONS: 20// <RET>

HSC NAME(S): <RET>

Installing/Configuring the VPM (continued):

NETWORK TOPOLOGY: <RET>

Edit? NO// <RET>

Select CM SITE NODENAMES: ISC

1 ISC6V0

2 ISC6V2

3 ISC6V4

CHOOSE 1-3: 1

NODENAME: ISC6V0// <RET>

NOTE: If you have already defined all nodes in version 7.2, be sure to update the new fields under this multiple for each node. The following information is required:

NODE-SPECIFIC BATCH QUEUE: ISC6V0\$BATCH// ??

Enter a node-specific batch queue for each node in this configuration. You must be running the 'SETUP...' option when defining this entry. If batch queues are defined for ALL nodes, com files will be built that submit jobs to these queues rather than using SYSMAN. An example of such a queue would be DSM\$BATCH_<nodename>. For example:

```
ISC6V0: sho que/full dsm$batch_isc6v0
Batch queue DSM$BATCH_ISC6V0, idle, on ISC6V0::
  /BASE_PRIORITY=4 /JOB_LIMIT=1 /OWNER=[SYSTEM]
  /PROTECTION=(S:E,O:D,G:R,W:W)
```

or

```
ISC6V0: sho que/full sys$batch
Batch queue ISC6V0$BATCH, available, on ISC6V0::
  /BASE_PRIORITY=4 /JOB_LIMIT=15 /OWNER=[SYSTEM]
  /PROTECTION=(S:E,O:D,G:R,W:RW)
```

If Taskman is configured to run from a dcl context, you may enter the queue TM\$nodename.

NODE-SPECIFIC BATCH QUEUE: ISC6V0\$BATCH// <RET>

USERNAME: TASKMAN// ??

Enter the name of a VMS user, such as TASKMAN, which has been previously added to UAF with sufficient privileges.

USERNAME: TASKMAN// <RET>

Installing/Configuring the VPM (continued):

```
DSM ENVIRONMENT MANAGER: ISCMGR// ??
```

The DSM ENVIRONMENT name will be that which is entered when logging into DSM. The name itself follows 'DSM/ENVIRONMENT=', ie,

```
$ dsm/environment=ABCMGR
```

If running taskman from a DCL context, this was defined in the TASKMAN SITE PARAMETERS as well. This field will be used by taskman when starting new RTHIST sessions.

```
DSM ENVIRONMENT MANAGER: ISCMGR// <RET>
```

```
Select CM SITE NODENAMES: <RET>
```

```
Requested Start Time: NOW// <RET>
```

One moment while I check/clean up MTLU variable pointers.
Done...

TO PROTECT THE SECURITY OF DHCP SYSTEMS, DISTRIBUTION OF THIS SOFTWARE FOR USE ON ANY OTHER COMPUTER SYSTEM IS PROHIBITED. ALL REQUESTS FOR COPIES OF THE KERNEL FOR NON-DHCP USE SHOULD BE REFERRED TO YOUR LOCAL ISC.

```
VAH,MTL>
```

If the VPM global conversion fails for any reason, it can be re-started by executing the routine, ^XUCINIT.

Using the TaskMan option, Schedule/Unschedule Options [ZTMSCHEDULE], queue XUCM TASK VPM to run hourly. This option is the data collection driver for the VMS monitor and checks for and loads new data into the CM DISK DRIVE RAW DATA (#8986.5) and CM NODENAME RAW DATA (#8986.51) files. Each data collection runs for 15 minutes. Queue the option XUCM TASK NIT to run in the early AM, (e.g., 0001 hours). This option compiles workday averages, mail server messages, and collects "static" information such as node and hardware types. Finally, this option files selected RTHIST data and restarts RTHIST data collections for the next 24 hours.

Installing/Configuring the MSM Performance Monitor (MPM)

NOTE: MSM Sites see the following dialogue as the MSM Performance Monitor is installed:

```
This version (#7.3) of 'XUCSINIT' was created on 18-MAY-1994
      (at CLARKSBURG 998, by VA FileMan V.20.0)

I AM GOING TO SET UP THE FOLLOWING FILES:

      8987.1      MSM RTHIST SITE
Note:  You already have the 'MSM RTHIST SITE' File.

      8987.2      MSM RTHIST REPORT DATA
Note:  You already have the 'MSM RTHIST REPORT DATA' File.

SHALL I WRITE OVER FILE SECURITY CODES? NO// <RET>  (NO)
NOTE: This package also contains INPUT TEMPLATES
      SHALL I WRITE OVER EXISTING INPUT TEMPLATES OF THE SAME NAME? YES//
<RET>  (YES)
NOTE: This package also contains PRINT TEMPLATES
      SHALL I WRITE OVER EXISTING PRINT TEMPLATES OF THE SAME NAME? YES//
<RET>  (YES)
NOTE: This package also contains OPTIONS
      SHALL I WRITE OVER EXISTING OPTIONS OF THE SAME NAME? YES// <RET>  (YES)

ARE YOU SURE EVERYTHING'S OK? NO// Y <RET>  (YES)

...EXCUSE ME, HOLD
ON.....
'XUCS MANAGER MENU' Option Filed
'XUCS MANUAL PURGE OF DATA' Option Filed
'XUCS REPORTS BY (DATE,VG)' Option Filed
'XUCS SITE EDIT' Option Filed
'XUCS SITE EDIT MENU' Option Filed
'XUCS SYS CONFIG PARMS DISPLAY' Option Filed
'XUCS VOL GROUP EDIT' Option Filed
'XUCSR REPORTS MENU' Option Filed
'XUCSRA CPU/DISK REPORT' Option Filed
'XUCSRA GREF REPORT' Option Filed
'XUCSRA REPORTS BY (VG,DATE)' Option Filed
'XUCSRA RESPONSE REPORT' Option Filed
'XUCSRA ROU CMNDS/GREF REPORT' Option Filed
'XUCSRA SYS STAT REPORT' Option Filed
'XUCSRB CPU/DISK REPORT' Option Filed
'XUCSRB GREF REPORT' Option Filed
'XUCSRB REPORTS BY (DATE,VG)' Option Filed
'XUCSRB RESPONSE REPORT' Option Filed
'XUCSRB ROU CMNDS/GREF REPORT' Option Filed
'XUCSRB SYS STAT REPORT' Option Filed
'XUCSRG CPU-DISK GRAPH' Option Filed
'XUCSRG GRAPHS MENU' Option Filed
'XUCSRG RESPONSE TIME GRAPH' Option Filed
'XUCSTASK AM RTHIST' Option Filed
```

Installing/Configuring the MPM (continued):

```
'XUCSTASK FILE UPDATE AUTO' Option Filed
'XUCSTASK PM RTHIST' Option Filed
'XUCSTASK PURGE CM DATA' Option Filed...
OK, I'M DONE.
NO SECURITY-CODE PROTECTION HAS BEEN MADE

One moment while I check/clean up MTLU variable pointers.
Done...

TO PROTECT THE SECURITY OF DHCP SYSTEMS, DISTRIBUTION OF THIS
SOFTWARE FOR USE ON ANY OTHER COMPUTER SYSTEM IS PROHIBITED.
ALL REQUESTS FOR COPIES OF THE KERNEL FOR NON-DHCP USE SHOULD
BE REFERRED TO YOUR LOCAL ISC.
NXT,KDE>
```


Configuration of the MSM Performance Monitor

The following steps are needed to complete configuration of the MSM performance monitor:

1. Distribute the following routines to the remaining COMPUTE and PRINT SERVERS:

```
XUCS*
-XUCSI*
ZOSV2MSM
Rename ZOSV2MSM to %ZOSV2
```

2. Move ZOSV2MSM to the MGR UCI of the **File Server(s)** and rename it to %ZOSV2.
3. Edit the MSM Site Parameters using the MSM Site Parameters Enter/Edit Menu option:

a. Edit MSM CM Site Parameters

```
Select MSM Capacity Management Manager's Menu Option: ?
```

```
    CM Reports Menu ...
    Manually Purge CM Data
    MSM Site Parameters Enter/Edit Menu ...
```

```
Select MSM Capacity Management Manager's Menu Option: MSM Site Parameters
Enter/Edit Menu
```

```
Select MSM Site Parameters Enter/Edit Menu Option: ?
```

```
  1      Edit MSM CM Site Parameters
  2      Enter/Edit Volume Group (Node)
  3      Print/Display System Configuration Parameters
```

```
Select MSM Site Parameters Enter/Edit Menu Option: 1 Edit MSM CM Site
Parameters
```

```
Select MSM RTHIST SITE SITE NAME: ???
```

```
    This is the name of your site. For example: SAN FRANCISCO VAMC
```

```
Select MSM RTHIST SITE SITE NAME: CLARKSBURG VAMC
```

```
ARE YOU ADDING 'CLARKSBURG VAMC' AS A NEW MSM RTHIST SITE (THE 1ST)? Y
```

```
<RET> (YES)
```

```
SITE NAME: CLARKSBURG VAMC// <RET>
```

```
SITE NUMBER: 540 ???
```

```
    This is your station number. For example, 662
```

```
SITE NUMBER: 540 <RET>
```

MSM Site Parameters Enter/Edit Menu (continued):

DFLT ROU NAME LENGTH: ???

This is a required field that is used by the Routine Report so that routines can be grouped by name. For example, if you enter a "3", then routine commands and routine global accesses will be grouped together by the first 3 characters of their name.

DFLT ROU NAME LENGTH: 4

DFLT GBL NAME LENGTH: ???

This is a required field that is used by the Global Report so that global accesses can be grouped. For example, if you enter a "3", then the global names will be grouped together by the first 3 characters of their name.

DFLT GBL NAME LENGTH: 4

<thresh ROU CMDS/SEC: ???

Some DHCP routines are executed very briefly. Therefore, the number of commands they execute are relatively very small for a RTHIST session. A "bucket" called '<thresh' in the Routine command report is where all command counts for these types of routine(s) will be collected. For example, if routine ABC executes 976 commands for a RTHIST session and you specify 1000 as the thresh hold value, then ABC's command count will be placed in the '<thresh' bucket.

<thresh ROU CMDS/SEC: 100

<thresh GBL GREFS/SEC: ???

Some DHCP routines reference global(s) very little. Therefore, the number of global references are relatively very small for a RTHIST session. A "bucket" called '<thresh' in the Global Access report is where all these type of global(s) will get placed. For example, if global ABC is referenced 109 times for a RTHIST session and you specify 300 as the threshold, the ABC's reference count will be placed in the '<thresh' bucket.

<thresh GBL GREFS/SEC: ?

Type a Number between 0 and 999999, 0 Decimal Digits

<thresh GBL GREFS/SEC: 100

DAYS TO KEEP DATA: ???

This field represents the number of days data will be kept in File #8987.2. If NULL, then 45 days is the used for the default.

DAYS TO KEEP DATA: <RET>

Select LOCAL CMP RECIPIENTS: DOE,JOHN

Select LOCAL CMP RECIPIENTS: <RET>

Select REMOTE CMP RECIPIENTS: (NOTE: Optional. You may be requested to send data to your ISC. If so, enter a mail group containing at least your ISC as a remote recipient.)

Select MSM RTHIST SITE SITE NAME: <RET>

b. Enter/Edit Volume Group (Node)

Select MSM Site Parameters Enter/Edit Menu Option: **2** Enter/Edit Volume Group (Node)

Select MSM RTHIST SITE SITE NAME: **`1** CLARKSBURG VAMC

Select VOL GROUP (NODE): **PSA**

ARE YOU ADDING 'PSA' AS A NEW VOL GROUP (NODE) (THE 1ST FOR THIS MSM RTHIST SITE)? **Y <RET>** (YES)

SERVER TYPE: **Print**

NAME OF MANAGER UCI: **MGR**

NAME OF PRODUCTION UCI: **VAH**

AUTO ADJUST RTHIST TABLE SIZE: **???**

Leave this field blank to AUTOMATICALLY ADJUST THE RTHIST TABLE SIZE. When the RTHIST job is started, it requires the number of table entries to be specified. If the entry for table size is too small, then a ~TABLE,FULL~ condition will occur. If you define this field (i.e. Not Null), then I will use this value for the MAXIMUM RTHIST table size. On the other hand, if you leave this field Null, then I will use the MAX AM TABLE SIZE field (#6) to adjust the AM RTHIST table size for the morning RTHIST session, or the MAX PM TABLE SIZE field (#7) to adjust the PM RTHIST table size for the afternoon RTHIST session.

AUTO ADJUST RTHIST TABLE SIZE: **<RET>**

Select MSM RTHIST SITE SITE NAME: CLARKSBURG VAMC **<RET>**

Select VOL GROUP (NODE): **PSA// CSA**

ARE YOU ADDING 'CSA' AS A NEW VOL GROUP (NODE) (THE 2ND FOR THIS MSM RTHIST SITE)? **Y <RET>** (YES)

SERVER TYPE: **Compute**

NAME OF MANAGER UCI: **MGR**

NAME OF PRODUCTION UCI: **VAH**

AUTO ADJUST RTHIST TABLE SIZE: **<RET>**

5. Using the TaskMan option, Schedule/Unschedule Options [ZTMSCHEDULE], schedule the following options:

XUCSTASK AM RTHIST

XUCSTASK PM RTHIST

XUCSTASK FILE UPDATE AUTO

XUCSTASK PURGE CM DATA

AM MSM RTHIST Task Option

```
NAME: XUCSTASK AM RTHIST                MENU TEXT: AM MSM RTHIST Task
Option
  TYPE: run routine                      CREATOR: POSTMASTER
  PACKAGE: MSM CAPACITY MANAGEMENT
  DESCRIPTION: This option is scheduled thru TaskMan's [ZTMSCHEDULE]
for the morning RTHIST data capture. It should be setup for a 1D
rescheduling frequency. NO output device is necessary.
  ROUTINE: XUCSTM
  QUEUED TO RUN AT WHAT TIME: MAY  3, 1994@08:30
  RESCHEDULING FREQUENCY: 1D             SCHEDULING RECOMMENDED: YES
  UPPERCASE MENU TEXT: AM MSM RTHIST TASK OPTION
```

PM MSM RTHIST Task Option

```
NAME: XUCSTASK PM RTHIST                MENU TEXT: PM MSM RTHIST Task
Option
  TYPE: run routine                      CREATOR: POSTMASTER
  PACKAGE: MSM CAPACITY MANAGEMENT
  DESCRIPTION: This option is scheduled thru TaskMan's [ZTMSCHEDULE]
for the afternoon RTHIST data capture. It should be setup as 1D
rescheduling frequency. No output device is necessary.
  ROUTINE: XUCSTM
  QUEUED TO RUN AT WHAT TIME: MAY  2, 1994@14:30
  RESCHEDULING FREQUENCY: 1D             SCHEDULING RECOMMENDED: YES
  UPPERCASE MENU TEXT: PM MSM RTHIST TASK OPTION
```

Tasked CM File Update

```

NAME: XUCSTASK FILE UPDATE AUTO           MENU TEXT: Tasked CM File Update
TYPE: run routine                         CREATOR: POSTMASTER
PACKAGE: MSM CAPACITY MANAGEMENT
DESCRIPTION: This option is scheduled thru TaskMan's [ZTMSCHEDULE].
It gathers the data from each Vol. Group defined in the MSM Site
Parameters file. It first transfers the PREVIOUS day's ^RTHIST data to
the %ZRTL("XUCS", nodes. It then formats the data into FileMan
compatible data, moving the data into the MSM RTHIST Data file.
Finally, it creates a server message to transmit a summary of the
PREVIOUS day's data to the National Data Base. It should be setup with
a 1 DAY rescheduling frequency. No output device is necessary, but you
might want to consider using a RESOURCE device, so that option XUCSTASK
PURGE CM DATA falls after this option.
ROUTINE: XUCSTME
QUEUED TO RUN AT WHAT TIME: MAY  3, 1994@01:00
DEVICE FOR QUEUED JOB OUTPUT: ZZRES;;132;66
RESCHEDULING FREQUENCY: 1D                SCHEDULING RECOMMENDED: YES
UPPERCASE MENU TEXT: TASKED CM FILE UPDATE

```

Auto Purge of CM Data

```

NAME: XUCSTASK PURGE CM DATA             MENU TEXT: Auto Purge of CM Data
TYPE: run routine                         CREATOR: POSTMASTER
PACKAGE: MSM CAPACITY MANAGEMENT
DESCRIPTION:

This is the schedulable TaskMan option to purge data from the MSM
RTHIST Data file . A selectable range of days to keep old data is in
the SITE file. If this is not filled in 45 days is the default. It is
recommended to schedule this option so that it is run AFTER the option
XUCSTASK FILE UPDATE AUTO. No output device is necessary, but might
want to consider using a RESOURCE device for ease of scheduling.

ROUTINE: DEQUE^XUCSPRG
QUEUED TO RUN AT WHAT TIME: MAY  3, 1994@03:00
DEVICE FOR QUEUED JOB OUTPUT: ZZRES;;132;66
RESCHEDULING FREQUENCY: 1D                SCHEDULING RECOMMENDED: YES
UPPERCASE MENU TEXT: AUTO PURGE OF CM DATA

```

NOTE: Any RTHIST that is *running* when either the AM or PM RTHIST is started will be stopped, as if it were stopped using the RTHIST - TERMINATE (SAVE).

Any RTHIST that is *scheduled* during the time period (1 hour) that is a scheduled AM or PM RTHIST will be unscheduled.

- **In MGR: Map routines in the Manager account.**

The recommended set is listed below:

%ZOSV
%ZOSV1
%ZOSV2

The following advisory is recommended:

- At a future time, you should review RTHIST data to identify the set of routines that are used most frequently at your site. The set provided here is only a "best guess" of which routines might be worth mapping.
- To avoid potential problems, do not map %ZOSV if you are running a version of VAX DSM less than V6.

DSM FOR OpenVMS

Edit your command file for building mapped routine sets, then run it.

MSM and M/SQL

Not Applicable

Shutdown DSM and Restart to Activate Mapped Sets

- **Shutdown and restart DSM**

Restart the configuration to activate the new set of mapped routines.

DSM for OpenVMS

Shut down and restart the configuration:

```
$ DSM/MAN ^SHUTDWN
```

and then

```
$ DSM/MAN ^STU
```

MSM and M/SQL

(Routine mapping is not applicable)

On the Other Toolkit V. 7.2 CPUs (MSM and M/SQL)

Steps that can be taken while inits run on the first CPU

- **Review the steps taken on the first CPU** and repeat those that apply.
- **In VAH:** Load all Toolkit V. 7.3 routines on this CPU, as you did on the first CPU.

Save the ZU routine corresponding to the current operating system. Move the relevant (Z*) routines to the Manager's account as on the first CPU. **Recall that MANAGER (%) routines for Kernel and FileMan were moved to a//MSM CPUs in preparation for the MSM Performance Monitor.**

- **In MGR:** Run TOOLKIT^ZTMGRSET as on the first CPU.
- **In VAH:** If the CPU runs a different MUMPS operating system, use the Reinitialize option on the VA FileMan Management Menu to identify the CPU's operating system, and thus, set the second piece of ^%ZOSF("OS") correctly. (NOTE: This menu is locked with the XUMGR key.) This step is necessary since, if ^DD is translated, ^DD("OS", a pointer to the MUMPS OPERATING SYSTEM file (#.7), indicates the operating system of the CPU where the DINIT was run.

After the inits have finished (VAX/Alpha)

- **Map routines:** For DSM for OpenVMS systems, rebuild the mapped routine set. Map routines in the Manager and Production accounts as on the first CPU. Remember to activate the new mapped routine sets.

Delete Inits

- **In VAH:** Optionally, delete the Toolkit init routines XUCIN*, XUCSI*, XTIN* using the ^%ZTRDEL utility to delete groups of routines.

Clear Obsolete Routines

The following routines have been identified as obsolete (no longer exported by the Toolkit). Please review against your own records and confirm that they are obsolete at your site before deleting them:

ZOSFM11	ZTCPU
ZOSVM11	ZTRTHM
ZTBKCM11	ZTRTHT

Clear Unused Routines from the Production Account

After running the Toolkit installation, the following routines may be deleted from the Production account where they were initially loaded (or any other Production account where they may have been loaded in the past):

ZO*	ZTMGRSET	ZTSYINIT
ZTBK*	ZTP1	
ZTEDIT*	ZTPP	
ZTGBL	ZTRDEL	

These routines may be deleted since, during the initialization process, they were saved to the Manager account where they become operative.

Install the VAX/ALPHA VMS EDT or TPU Text Editor (Optional)

Sites running DSM for OpenVMS may choose to install the VMS EDT and/or TPU text editors. This is accomplished by making an entry in the ALTERNATE EDITOR file (#1.2) as shown here.

```
>D Q^DI This entry point may be used to maintain device handler
      variables.

VA FileMan 20

Select OPTION: ENTER OR EDIT FILE ENTRIES

INPUT TO WHAT FILE: 1.2 ALTERNATE EDITOR (2 entries)
EDIT WHICH FIELD: ALL// <RET>

Select ALTERNATE EDITOR: VMSEDT
  ARE YOU ADDING 'VMSEDT' AS A NEW ALTERNATE EDITOR (THE 3RD)? Y (YES)
ACTIVATION CODE FROM DIWE: G ^XTEDTVXD (for the EDT editor)
ACTIVATION CODE FROM DIWE: G TPU^XTEDTVXD (for the TPU editor)
OK TO RUN TEST: I ^%ZOSF("OS")["VAX"
RETURN TO CALLING EDITOR: <RET>
DESCRIPTION:
  1> Call to VAX/ALPHA VMS EDT editor to process VA FileMan word-processing
fields.<RET>
  2> Creates a temporary VMS file in the default directory with a name <RET>
  3> of 'DIWE$'_ $JOB_'.TMP'. This version will remove the two copies <RET>
  4> of the file that EDT leaves behind. <RET>
  5> <RET>
EDIT Option: <RET>

Select ALTERNATE EDITOR: <RET>
```

Install the Kermit Protocol (Optional)

Kermit may be added to the ALTERNATE EDITOR file (#1.2) as shown. This allows the transfer of files from a PC, or other system, into a mail message or other VA FileMan word-processing field. Be sure that the file to be sent is in text-only format. Be sure that if a DEC server is involved, its break character is not a printable character, like ~, since Kermit uses all the printable characters when processing.

The benefit of using the Kermit file transfer protocol is that large files can be sent faster and more easily due to the efficient Kermit error checking mechanism.

```
>D Q^DI This entry point may be used to maintain device handler variables.

VA FileMan 20

Select OPTION: ENTER OR EDIT FILE ENTRIES

INPUT TO WHAT FILE: 1.2 <RET> ALTERNATE EDITOR (3 entries)
EDIT WHICH FIELD: ALL// <RET>

Select ALTERNATE EDITOR: KERMIT LOAD
  ARE YOU ADDING 'KERMIT LOAD' AS A NEW ALTERNATE EDITOR (THE 4TH)? Y (YES)
ACTIVATION CODE FROM DIWE: S XTKDIC=DIC D RECEIVE^XTKERMIT
OK TO RUN TEST: <RET>
RETURN TO CALLING EDITOR: K XTKDIC
DESCRIPTION:
  1> This option uses the KERMIT protocol to load the word-processing field
  <RET>
  2> from another system. <RET>
```

Bulletins Exported with Toolkit V. 7.3 (Not Associated with Mail Groups)

The following three Bulletins are a part of the Duplicate Resolution Utilities exported with Toolkit V. 7.3. They do *not* come with a mail group. You may associate them with any mail group you like. They are listed as follows:

XDR ERROR

This bulletin is sent to a mail group of your choice when something in the merge process errors out, is missing, or simply did not complete. The following is a list of all reasons that can trigger the sending of XDR ERROR bulletins:

- The Candidate Collection Routine is undefined.
- The Candidate Collection Routine is not present.
- The Potential Duplicate Threshold is undefined.
- There are no Duplicate Tests entered for this Duplicate Resolution entry.
- The Global root node in DIC is undefined.
- No entry in DUPLICATE RESOLUTION (#15.1) file for this file.
- The From and To Record are undefined.
- The test routine is not present.
- The routine defined as the Pre-Merge routine is not present.
- The routine defined as the Post-Merge routine is not present.
- The routine defined as the Verified Msg routine is not present.
- The routine defined as the Merged Msg routine is not present.
- You cannot have a "Non-Interactive" merge style with entries in the DINUM files multiple.
- The file for checking duplicates is not defined (XDRFL).
- The entry for checking duplicates is not defined (XDRCD).
- The routine defined as the Merge Direction Input Transform routine is not present.

- The *new* cross-reference has not been entered for this Duplicate Resolution entry.

XDR MERGED

This bulletin is a notification that all verified duplicate record pairs have been merged.

XDR VERIFIED

This bulletin is a notification that a pair of records have been verified as duplicates and are ready to be merged.

Index

A

ACL

- Environment Access Utilities 11
- Alternate Editor 61
- ALTERNATE EDITOR file 61, 62
- AM MSM RTHIST Task Option 52
- Auto Purge of CM Data Option 53

B

- Batch Queues, verify created 13
- Bulletins 63

C

- CM DISK DRIVE RAW DATA file 46
- CM METRICS file 43, 44
- CM NODENAME RAW DATA file 46
- CM SITE PARAMETERS file 13
- COMPUTE SERVER
 - Mode of TaskMan 17
- Configuration of the MSM
 - Performance Monitor 49
- Configuring TaskMan to run in a DCL Context 10

D

- DCL Context 9, 10, 45, 46
- DCL files 9
- DEVICE file 14
- Devices 14
- DINUM files
 - multiple 63
- DUPLICATE RESOLUTION file 63
- Duplicate Resolution Utilities 63

E

- Enter/Edit Volume Group (Node) 51

F

- FAILED ACCESS ATTEMPT LOG file 28
- File/Shadow Servers 15

G

- G.CMP@ISC-SF.VA.GOV
 - Mail Group 13
- ^%GDEL 15
- Global Placement 7, 15
- Global Protection 1, 8, 15, 31
- Global Translation 15, 16

H

- HFS Device 14

I

- %INDEX 6, 28, 30
- Init
 - Example Done at the San Francisco ISC 35-48
- Integrity Checking 7, 22

K

- K71PAT40.RTN file 3
- Kermit file transfer protocol 62
- Kernel 7.1 patch 40 3, 4
- KTK7_3.RTN file 3

M

Mail Groups

G.CMP@ISC-SF.VA.GOV 13

Manager Setup Routine

Example Done at the San Francisco ISC 29-30

Mapping Routines 21, 54, 55, 57

Morning RTHIST Data Capture 52

MSM Performance Monitor (MPM) 2, 7, 8, 15, 17, 51

Sample Install 47

Multi-Term Look-Up (MTLU) 2, 7, 20, 48

MUMPS OPERATING SYSTEM file 57

N

New Fields 45

New Global

^XUCS 2, 7, 8, 15, 32

New Mail Groups

G.CMP@ISC-SF.VA.GOV 13

NTEG Routine 7, 22

O

Obsolete Routines 59

OPER

VMS Privileges 9

P

Partition Size 33

^%PARTSIZ 33

PM MSM RTHIST Task Option 52

PROGRAMMER MODE LOG file 28

R

^%RD 7

Routine Restore

Example Done at the San Francisco ISC 23-24

Routine Save

Example Done at the San Francisco ISC 26

RTHIST 15, 46, 53, 54

S

Schedule/Unschedule options 46, 51

Symbol Table Size 19, 33

SYSSINPUT Device 14

SYSRV

VMS Privileges 9, 11

T

Tasked CM File Update Option 53

TaskMan 9, 10, 11, 12, 15, 19, 43, 46, 51, 52, 53

TASKMAN SITE PARAMETERS file 9, 17, 18

Text Editor

TPU 61

VMS EDT 61

TOOLKIT^ZTMGRSET 3, 28, 29, 57

TPU Text Editor 61

U

UCI ASSOCIATION file 17, 18

Unused Routines 3, 60

V

VAX/Alpha Performance Monitor

(VPM) 2, 7, 9, 13, 41, 42, 43, 44, 45, 46

Verify Created Batch Queues 13

VMS EDT Text Editor 61

VMS Privileges

OPER 9

SYSRV 9, 11

VOLUME SET file 17, 18

X

XDR ERROR bulletins 63
 XDR MERGED bulletins 64
 XDR VERIFIED bulletins 64
 ^XINDEX 6
 ^XMB Global 28
 ^XT 2, 7, 8, 15, 32
 ^XTMP 2
 XTNTEG 7, 22
 ^XUCINIT 46
 ^XUCM 2, 7, 8, 15, 32
 XUCM TASK NIT 20, 46
 XUCM TASK VPM 20, 46
 ^XUCMTM 9
 Example 10
 ^XUCP 2
 ^XUCS 2, 7, 8, 15, 32
 XUCSTASK AM RTHIST 52
 XUCSTASK FILE UPDATE AUTO 53
 XUCSTASK PM RTHIST 52
 XUCSTASK PURGE CM DATA 53
 XUMGR key 57
 XUPROG 20
 XUSITEMGR 20

Z

^%Z editor 28, 30
 ZINDEX* Routines 6
 ^%ZOSF 3, 15, 16, 28, 29, 57, 61
 ZOSV 4
 %ZOSV 3, 29, 54
 ^%ZRTL 31, 53
 ZTBK 4, 60
 ^ZTLOAD 9
 ZTMGRSET 3, 4, 16, 26, 28, 29, 57, 59,
 60
 ZTMSCHEDULE 46
 ^%ZTRDEL 58
 ^%ZUA 28

Department of Veterans Affairs
Decentralized Hospital Computer Program

KERNEL TOOLKIT INSTALLATION GUIDE

Version 7.3

April 1995

Information Systems Center
San Francisco, California

Table of Contents

Introduction	1
New Globals	2
Installing Toolkit V. 7.3	3
Preliminary Considerations	3
MSM Sites	6
Advance Preparation	7
VAX/ALPHA Installations	9
Sample Dialogue of Running ^XUCMTM.....	10
MSM-PC Installations.....	15
Begin the Installation.....	19
Read the Routines into Production	22
Move Routines to the Manager Account	25
Run the Manager Setup Routine	28
Review Global Protection for ^%ZRTL.....	31
Establish Global Translation	32
Do the First Part of the Installation.....	33
Example of an Init Done at the San Francisco ISC.....	35
Installing/Configuring the VAX/Alpha Performance Monitor (VPM)	41
Installing/Configuring the MSM Performance Monitor (MPM)	47
Shutdown DSM and Restart to Activate Mapped Sets	55
On the Other Toolkit V. 7.2 CPUs (MSM and M/SQL)	57
Steps that can be taken while inits run on the first CPU	57
After the inits have finished (VAX/Alpha).....	57
Delete Inits.....	58
Clear Obsolete Routines	59
Clear Unused Routines from the Production Account.....	60
Install the VAX/ALPHA VMS EDT or TPU Text Editor (Optional)	61
Install the Kermit Protocol (Optional)	62
Bulletins Exported with Toolkit V. 7.3 (Not Associated with Mail Groups) ..	63
Index	65

Table of Contents